



[www.zygon.ca](http://www.zygon.ca)

| [info@zygon.ca](mailto:info@zygon.ca)



# ZHC-200 ABA

## HIGH SPEED CENTRIFUGE



## High Speed Centrifuge

- Microcomputer control, LCD liquid crystal display (LCD)
- AC frequency conversion motor drive, quiet operation clean.
- Offers nine ascending and descending rate selection mode, Offer ten kinds of working mode selection, can free programming call.
- Speed/centrifugal force can be set and double synchronous display screen
- Two optional timing mode: run start timing and timing starts to set speed, easy to switch.
- Door with double lock rod design, magnetic locks, electric door, more safety and reliable operation
- Can change at any time in the operation of the parameters without downtime
- Unique design of air exhaust temperature, low noise
- Automatic identification of 9.Turn
- Turned to use memory function, turned to the service life of the machine will alarm prompt, prevent the security hidden danger.

### Specifications

### ZHC-200 ABA

Maximum Speed	21000 rpm
Maximum RCF	23198xg
Speed Accuracy	±100rpm
Noise	≤55dB
Timer Range	1min ~99:99:59(hh:mm:ss)
Temperature Indicators	≤8°C (running 20 minutes)

Power Supply	AC 220V 50Hz
Power	550VA
Weight	50kg
Dimensions (LxWxH)mm	373x510x405

## Optional Rotors

No.	Rotor Capacity	Max Speed	Max RCF
1	12×0.5ml	21000rpm	22182× g
2	24×1.5ml/2.2ml	16000rpm	20049× g
3	12×1.5ml/2.2ml	18000rpm	23198× g
4	12×5ml	16000rpm	17459× g
5	12×10ml	14000rpm	18188× g
6	48×0.5ml	16000rpm	21504× g
7	36×1.5ml/2.2ml	14000rpm	17749× g
8	8×15ml	12000rpm	14170× g
9	6×50ml	12000rpm	16099× g
10	6×100ml	10000rpm	10170× g
11	4×85ml	5000rpm	3830× g