

zygon

www.zygon.ca

| info@zygon.ca



ZMM-200 BBI METALLURGICAL MICROSCOPE



Inverted Metallurgical Microscope, BF/DF, DIC, Polarizing

- Modularization Function Design Polarizing View For Metallurgical Lab
- LWD Infinity BD Plan Objective (No Cover Glass) For DIC
- Epi Illumination Integrate Field Diaphragm, Aperture Diaphragm, Filters Switching Device For Y,B,G And Ground Glass Filters
- Transmit & Reflect Halogen Light Source For Metallurgical Observe

Specifications

ZMM-200 BBI

Head	Binocular Head, Inclination 45°, Interpupillary Distance 53~75mm
Eyepiece	WF10x/22mm
Nosepiece	Quintuple, Ball Bearing Inner Locating
LWD Infinity Bright Field Plan Objective (No Cover Glass)	PLL10x/0.25mm, W.D.20.2mm PLL20x/0.40mm, W.D.8.8mm PLL50x/0.70mm, W.D.3.68mm, Spring PLL100x/0.85mm, W.D.0.4mm, Spring
Working Stage	Double Layer Mechanical Stage, Size 242x200mm, Moving Range 30x30mm, Round Rotatable Stage Max Measurement Dia.130mm, Minimum Clear Aperture Less Than Dia.20mm
Focusing	Coaxial Coarse & Fine Focus, With Tension Adjustment And Up Stop, Fine Focusing Minimum Division 2μm
Reflect Illumination	6V30W Halogen Lamp, Brightness Adjustable Epi Illumination Integrate Field Diaphragm, Aperture Diaphragm, Filter Switching Device For Yellow, Blue, Green Filter & Ground Glass
Polarizing	Push-Pull Type Polarizer Built-in Analyzer And Switching Freely

Optional Accessories

Specifications

ZMM-200 BBI

Eyepiece	Dividing WF10x/22mm, 0.1mm/Div
LWD Infinity Bright Field Plan Objective (No Cover Glass)	PLL2.5x/0.07mm, W.D.13mm PLL5x/0.12mm, W.D.26.1mm PLL40x/0.60mm, W.D.3.98mm, Spring PLL60x/0.70mm, W.D.3.18mm, Spring PLL80x/0.80mm, W.D.1.25mm, Spring
Adapter	0.4x C-Mount 1.0x C-Mount 0.5x C-Mount With Dividing 0.1mm/Div 0.5x C-Mount Digital SLR Camera Adapter for Canon EF