




www.zygon.ca

| info@zygon.ca



ZMS-100 ADH

MAGNETIC STIRRER



Magnetic Stirrer

- Stretched shell and cover prevents leaking.
- Heating and stirring can proceed simultaneously.
- Temperature setting is precise. And stirring speed stepless is adjustable.
- Large LCD display,
- Temperature and rotate speed can be displayed simultaneously.
- Double sensors: Outer PT100 temperature sensor to control liquid temperature precisely, inner K model sensor to control hot plate temperature.
- K mode sensor to control hot plate temperature.

Specifications

ZMS-100 ADH

Mode	Digital + Heating + Stirring
Max. Volume (ml)	5000
Speed (R.P.M)	200~2000
Working time	Continuous
Minimum revolution (R.P.M.)	200
Max. Temperature (°C)	350
Exterior	Iron plate welding, surface spraying
Heating plate	Ceramic Coated
Driving mode	Motor

Specifications

ZMS-100 ADH

Motor power (W)	20
Heating power (kW)	0.6
Stir bar	PTFE
Continuous operation	Yes
Setting mode	Digital
Speed display mode	Digital
Timer	No
Operation function	No
Sensor	PT100
Exterior size(WxLxH)	320 × 190 × 125mm
Packing size(WxLxH)	390 × 240 × 230mm
Plate size(mm)	190 × 190
Plate load	10kg
Power supply (50/60Hz) Current rating	110V or 220V
NW/GW (kg)	5/6