



ZTA-50 A

TABLE TOP STEAM STERILIZER

Table Top Steam Sterilizer

ZTA-50 A

ZTA-50 A is a Table Top Steam Sterilizer that is easy to operate, safe and reliable. It comes equipped with an in-built printer, which records the full procedure of the sterilization. It also self-tests malfunction, and is easy to maintain.



The sterilizing procedure is automatically controlled and does not require supervision



The unit won't start if the water doesn't reach the high level, and the power will cut off directly



Drying function



Over temperature and over pressure auto-protection



Door safety lock system. Pressure in the chamber must be less than 0.027MPa for the door to be opened



Over pressure protection: If the pressure exceeds the working pressure, the safety valve will exhaust the air



Over-current protection: The breaker will cut off the power in case of over-current



Provides 3 or more times pulse-vacuum exhausting, applied to wrapped or unwrapped objects, hollow equipment



With Bowie & Dick testing function for steam penetration testing



Specifications

ZTA-50 A

Chamber Volume	50 L
Max Working Pressure	0.22MPa
Max Working Temperature	134°C±1°C
Adjusted Sterilizing Temperature Range	55~134°C
Adjusted Timer Range	1-99 min
Adjusted Drying Time Range	1-99 min
Vacuum Limit	-0.08MPa
Heat Average	≤2°C
Power Supply	AC220V/50HZ
Dimension	770*600*540 mm