



ZSC-200 AAB BIOLOGICAL SAFETY CABINET



Product Description

ZSC series biological safety cabinets are biological safety isolation equipment used in biological safety laboratories or other laboratories to protect personnel, tested samples and the environment. It can meet the operation of pathogenic body with risk level of 1, 2 and 3.

Product Features

High-Quality & Ergonomic Construction

- The box body is made of high-quality SUS304 stainless steel or cold-rolled steel plate, which is easy to clean;
- The exhaust air is filtered by a high-efficiency filter to protect the environment from pollution;

Energy-efficient

- Class II biological safety cabinet.
- Vertical laminar negative pressure model, return air 30%/100% filtration discharge;

High security

- Negative pressure design ensures the safety of operators;
- Integrated sliding safety door positioning, easy to operate;
- Equipped with filter blocking alarm, blower overload alarm, working window opening limit alarm system;

Cleanliness level ISO level 5 (Level 100)

Classification Class II Type A2

Filter level / filter efficiency HEPA/ULPA ≥99.995~99.999% @0.3μm

Average flow rate of downdraft(m/s) $0.25 \sim 0.40$

Average flow rate of inflow air(m/s) ≥ 0.5

Sound emission (dBA) ≤67

Vibration peak (μm) ≤5

Electricity AC single-phase 220V/50Hz

Air balance biological protection Personnel protection: a.) The total number of colonies in the

impact sampler: ≤10CFU/time

b.) Total colony count of the slot sampler: ≤5CFU/time Product protection 1-8CFU/ml (repeat 3 times, 5min/time)

total number of colonies: ≤5CFU/time

Cross contamination protection 1-8CFU/ml (repeat 3 times,

5min/time) total number of colonies: ≤5CFU/time

Max power (KV·A) ≤1.5 (Spare socket included)

Weight (Kg) 230/240

Working zone size (W*D*H) 1000*520*640 mm

External dimensions (W*D*H) 1165*760*2200 mm

Fluorescent lamp 20W*2pcs

UV lamp 18W*1pc

Illumination (Lux) 650

Supply and exhaust pipe diameter(mm) Φ 250

Wind direction Top out