



## **ZVA-101 EL**ELECTRIC-HEATED VERTICAL STEAM STERILIZER



## Steam Sterilizer

- Automatically controlled by computer, digital display of working status, touch type key.
- Dynamically showed the temperature, pressure time and vacuum rate and the full cycle
- Fully automatically route for water inlet, pulse vacuum, heating, sterilizing, draining, exhausting, vacuum drying.
- 3 times pulse vacuum, which make the vacuum rate as -0.081 mpa, and ensure the high extracting of inner air from dressing, A.B type hollowed appliance.
- With 4 fixed program for appliance, medical dressing, rubbers and fluid, and the user can also set the program as they need.
- Equipped with the PT/TT testing connector, easy to run the testing.
- Multiple pulse vacuum drying after sterilizing, ensure the nice sterilizing.
- Equipped with bacteria filter, ensure the sterile air enter the inner vacuum environment, avoid the second contamination.
- Hand wheel type of quick-open door structure, self-inflating type seal.
- Adopted with immersed heating, with high heating efficiency.
- Steam-water inner circulation system:no steam discharge, and the environment for sterilizing will be clean and dry.
- Automatically shut off with beep reminding after sterilization.
- Fully high quality stainless, equipped with double stainless steel basket.

Specifications	ZVA-101 EL
Volume (L)	100 (φ440×650mm)
Working Pressure	0.22MPa
Working Temperature (°C)	134
Heat Average	≤±1°C
Timer	0~99min

<b>Specifications</b>	ZVA-101 EL

Adjustment of Tempertature 105~134°C

Power 4.5Kw/AC220V 50Hz

Overall Dimension (mm)  $750 \times 550 \times 1350$ 

Transport Dimension (mm)  $840 \times 640 \times 1410$ 

Gross Weight/ Net Weight 160 kg/ 128 kg