

zygon

www.zygon.ca

info@zygon.ca



ZTM-102 AAA

TDS METER



TDS Meter

- 1 point push-button calibration allows using the custom calibration solution
- Hold function momentarily freezes reading for easy viewing and recording
- Replaceable electrode module reduces maintenance and replacement cost
- Auto-Power Off effectively conserves battery life

Specifications

ZTM-102 AAA

| | |
|--------------------------|----------------------------------|
| Range | 5~1000ppm |
| Resolution | 1ppm |
| Accuracy | ±1% F.S. |
| Calibration Points | 1 point |
| Range | 0~50°C |
| Resolution | 1°C |
| Accuracy | ±1°C |
| Offset Calibration | — |
| Temperature Compensation | 0~50°C, automatic |
| TDS Factor | 0.4~1.0 (default 0.5) |
| Hold Function | Manual |
| Auto-Off | 8 minutes after last key pressed |

| | |
|-----------------------|---|
| Operating Temperature | 0~50°C |
| Display | Single-line LCD (21 x21mm) |
| Power Requirements | 3x1.5V LR44 micro alkaline batteries |
| Battery Life | Approximately 150 hours of continuous use |
| Dimensions | 185 (L) x 40 (Dia.) mm |
| Weight | 100g |