



ZTA-23 B TABLETOP AUTOCLAVE



Tabletop Autoclave

This series of autoclave offers high performance, reliability, safety and it is specially designed to meet the EN13060 European standards. Type B is suitable for packaging, unpacking, solid, A type hollow, B class hollow, B class hollow porous and internal pipeline, liquid.

- High-quality stainless steel liner, airtight cover
- Microcomputer control
- Safety interlock device
- BD test, HELIX test, Vacuum test
- LCD liquid crystal display, touch key
- Equipped with standard test interface
- Open overhead water tank
- European class B standard
- Automatic protection function: over temperature protection; over pressure protection; low water level protection, anti-dry burning; safety door lock
- Triple pulsating vacuum
- Buzzer reminder when sterilization is over, automatic shutdown
- Automatically discharge cold air, and automatically discharge steam after sterilization
- Built-in steam generator to quickly provide saturated steam
- Optional external (internal) built-in printer
- Optional USB function and U disk

Volume	23L
Power	2.2kW
Voltage	110V/220V, 60/50HZ
Rated Working Pressure	0.22mpa
Rated Working Temperature	134°C
Chamber Volume	250 × 452
Outer Dimension	480 × 690 × 450 mm
Packing Size (L \times W \times H)	760 × 560 × 510 mm

ZTA-23 B

60/53 kg

Specifications

Gross/ Net Weight