



## **ZVA-75 XL**VERTICAL AUTOCLAVE



## **Electric-Heated Vertical Steam Sterilizer**

- Automatically controlled by computer, digital display of working status, touch type key.
- Dynamically shows the temperature, pressure time and vacuum rate and the full cycle
- Fully automatic route for water inlet, pulse vacuum, heating, sterilizing, draining, exhausting, vacuum drying.
- 3 times pulse vacuum, which makes the vacuum rate as -0.081mpa, and ensures the high extracting of inner air from dressing, A.B type hollowed appliance.
- With 4 fixed program for appliance, medical dressing, rubbers and fluid, and the user can also set the program as they need.
- Equipped with the PT/TT testing connector, easy to run the testing.
- Multiple pulse vacuum drying after sterilizing, ensure the nice sterilizing.
- Equipped with bacteria filter, ensure the sterile air enter the inner vacuum environment, avoid the second contamination.
- Hand wheel type of quick-open door structure, self-inflating type seal.
- Adopted with immersed heating, with high heating efficiency.
- Steam-water inner circulation system:no steam discharge, and the environment for sterilizing will be clean and dry.
- Automatically shuts off with beep reminding after sterilization.
- Fully high quality stainless, equipped with double stainless steel basket.

Specifications	ZVA-75 XL	
Chamber Volume	75L(φ400×600)mm	
Working Pressure	0.22MPa	
Working Temperature	134°C	
Heat Average	≤±1°C	

6			
51	pecif	ıcatı	ions

## ZVA-75 XL

Timer 0~99min

Adjustment of Temperature 105~134°C

**Power** 4.5KW /AC220V.50Hz

Overall Dimension  $730 \times 510 \times 1270 \text{(mm)}$ 

Transport Dimension  $820 \times 600 \times 1380 \text{(mm)}$ 

**G.W/N.W** 140Kg/ 118Kg